

Applicant : Matthew Seelig et al.

Date: 11/30/06

Serial No. : 10/813,914

Art Unit: 3733

Response to Office Action of August 30, 2006

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1(currently amended). An instrument for gripping an orthopaedic fixation pin during a surgical procedure and extracting the pin from bone in which the pin is embedded, the pin having an embedded portion extending into the bone along a longitudinal axis, and a projecting portion projecting longitudinally from the bone adjacent a bearing surface associated with the bone, the instrument comprising:

a first handle member;

a second handle member coupled with the first handle member for selective movement relative to the first handle member between a first position and a second position;

a pusher coupled with the first and second handle members for movement relative to the first and second handle members in directions along a linear path essentially parallel to the longitudinal axis in response to movement of the second handle member between the first and second positions; and

a gripping mechanism including first and second gripping elements coupled with the first and second handle members for movement to grip the projecting portion of the pin between the first gripping element and the second gripping element in response to an

Applicant : Matthew Seelig et al.

Date: 11/30/06

Serial No. : 10/813,914

Art Unit: 3733

Response to Office Action of August 30, 2006

initial movement of the second handle member from the first position toward a second position;

the first gripping element including a gripping surface integral with the first handle member;

the second gripping element including a gripping finger mounted upon the first handle member for movement toward and away from the gripping surface; and

a linkage system coupling the second handle member with the gripping finger for movement of the gripping finger laterally toward the gripping surface in response to movement of the second handle member from the first position toward the second position;

the second handle member being coupled to the pusher such that upon movement of the second handle member relative to the first handle member farther toward the second position, subsequent to the initial movement, the pusher is urged against the bearing surface to move the gripping mechanism away from the bearing surface and to establish an extraction force in a direction essentially parallel to the longitudinal axis, and the gripped projecting portion of the pin is moved with the gripping mechanism to withdraw the embedded portion of the pin from the bone along a direction essentially parallel to the longitudinal axis.

Applicant : Matthew Seelig et al.

Date: 11/30/06

Serial No. : 10/813,914

Art Unit: 3733

Response to Office Action of August 30, 2006

2(original). The instrument of claim 1 wherein the pusher comprises a plunger mounted upon the first handle member for sliding movement in directions essentially parallel to the longitudinal direction.

3(original). The instrument of claim 1 wherein the second handle member is mounted for pivotal movement relative to the first handle member.

4(canceled).

5(canceled).

6(currently amended). The instrument of claim [[5]] 2 wherein the gripping surface includes a first contour configuration, and the plunger has a second contour configuration, the first and second contour configurations being dimensioned and configured for essentially confining the pin closely between the gripping surface and the plunger.

7(previously presented). The instrument of claim 6 wherein the first and second contour configurations each comprise a partially cylindrical contour configuration.

Applicant : Matthew Seelig et al.

Date: 11/30/06

Serial No. : 10/813,914

Art Unit: 3733

Response to Office Action of August 30, 2006

8(currently amended). The instrument of claim [[5]] 2 wherein the plunger is mounted for movement between a retracted position, wherein the plunger is retracted toward the first handle member, and an advanced position, wherein the plunger is advanced from the first handle member against the bearing surface, the instrument including:

a biasing mechanism for biasing the plunger toward the retracted position with a predetermined biasing force; and

an actuator carried by the second handle member for urging the plunger toward the advanced position, against the predetermined biasing force of the biasing mechanism, in response to movement of the second handle member from the first position toward the second position.

9(original). The instrument of claim 8 wherein the linkage system is configured for urging the gripping finger toward the gripping surface to establish a gripping force, in response the initial movement of the second handle member toward the first handle member, and for urging the plunger toward the advanced position to establish an extraction force in response to movement of the second handle member beyond the initial movement toward the second position, with the gripping force established prior to establishment of the extraction force, by virtue of the predetermined biasing force.

Applicant : Matthew Seelig et al.

Date: 11/30/06

Serial No. : 10/813,914

Art Unit: 3733

Response to Office Action of August 30, 2006

10(original). The instrument of claim 9 wherein the actuator includes an arm on the second handle member, the arm being coupled with the biasing mechanism such that the biasing mechanism biases the second handle member toward the first position.

11(original). The instrument of claim 10 wherein the biasing member includes a spring positioned and configured for biasing the plunger toward the retracted position and the second handle member toward the first position.

12(canceled).

13(canceled).

14(canceled).